

SET LAUFEN PRO NORDICS

Floorstanding WC combination with cistern without fixing holes for floor fixation 82795.3



TECHNICAL DATA

Order no.	82795.3
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 780 with cistern flushing mechanism Impuls 720, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 781
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	34,5 kg
Accessories excl.	Seat and cover, order no. 89095.2 Seat and cover with automatic lowering system, order no. 89095.3

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC pan washdown LAUFEN PRO NORDICS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush) EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 450 mm outlet horizontal, VARIO vertical 70 - 250 mm, back to wall
Special feature: concealed surfaces directing water are fully glazed throughout, closed water rim, vacuum checked
Further options / accessories: Surface refinement LCC, with shut-off valve option 781, WC seat and cover, 89095.2, WC seat and cover with automatic lowering 89095.3
Order no. 82795.3

TECHNICAL DRAWINGS / S 1 : 20

